

Giada MI-6200SL

6th Generation Intel® Core™ CPU Solution



Features

- Intel® Core™ i5-6200U Processor, 2.3 GHz (up to 2.8 GHz)
- 2 x 204-pin SO-DIMMs, DDR3L-1333MHz, up to 16 GB
- 1 x HDMI, 1 x DVI, 1 x LVDS
- 1 x mSATAIII, 1 x SATAIII,
- 1 x Mini-PCIe, 1 x SIM
- 1 x USB3.0, 1 x USB2.0, 2 x COM, 2 x RJ45

Core System

CPU	Intel® Core™ i5-6200U Processor, 2.3 GHz (up to 2.8 GHz)
System Memory	2 x 204-pin SO-DIMMs, DDR3L-1333MHz, up to 16 GB
Chipset	Integrated
BIOS	AMI EFI 64 Mbit
SSD	1 x mSATAIII, 2 x SATAIII
JAHC (Patented Tech)	WatchDog Timer, Auto Power On, RTC, Power Remote Control, Wake On Lan
H/W Monitor	Yes
Expansion Interface	1 x Mini-PCIe, 1 x SIM

Mechanical and Environmental

Dimensions	170mm x 170mm
Power Requirement	12V-19V
Operating Temperature	0~60°C at 0.7m/s air flow
Storage Temperature	-20°C~75°C
Relative Humidity	95%@40°C (non-condensing)

I/O

MIO	2 x COM (2 x 9Pin Com Header)
SATA	1 x mSATAIII, 2 x SATAIII
Ethernet	1 x RJ45
Audio	Realtek ALC662-VD, High Definition Audio (HD), 1 x MIC-IN, 1 x AUDIO-OUT
USB	4 x USB3.0(2 x USB3.0 external, 2 x USB3.0 header) 4 x USB2.0(2 x USB2.0 external, 2 x USB2.0 header)

Ordering Information

MI-6200SL	Intel® Core™ i5-6200U Processor, 2.3 GHz (up to 2.8 GHz), DDR3L-1333MHz, up to 16 GB, 4 x USB3.0, 4 x USB2.0, 1 x mSATAIII, 2 x SATAIII, 1 x RJ45, HDMI/DVI/LVDS
-----------	--

Display

Display Chipset	Integrated Intel® HD Graphics 520
Memory Size	Share System Memory
Display Interface	1 x HDMI (Max. 4096 x 2304 @24fps) 1 x DVI (Max. 2560 x 1600 @60fps) 1 x LVDS (Default 1920 x1080, 5V)

Dimensions and Drawing

